



PET SHEET

July 2012



MPX 4300 PETEWICH®

Recycled PET capped in virgin polymer
Eco-Efficient Packaging

CAPABILITIES

- Gauge: .014" to .035" (356 to 889 µm)
- Width: 12" to 48" (305 to 1219 mm)
- Core Size: 6" standard cores, 3" and 8" available
- Roll O.D.: 29" standard, up to 40" available
- Recycled content
- Silicone coating available
- Clear, custom translucent and opaque colors
- 2 manufacturing locations

PROPERTIES

- Appropriate for packaging & holding fresh fruits and vegetables at room temperature and below
- Good Clarity
- Excellent surface quality
- Improved economics for food content packaging
- 100% recyclable
- Kosher material

TECHNICAL SPECIFICATIONS

	Value	Units	ASTM
Density	1.33	g/cc	
Shrinkage	2.0 to 5.0	%	D955
Yield	20,810	in ² /lb./mil of thickness	
Tensile Strength at Yield	7,500 to 8,500	psi	D638
Ultimate Elongation	100 to 300	%	D638
Flexural Modulus	325,000 to 370,000	psi	D790
Intrinsic Viscosity	≥0.66		D3835
Light Transmission	>85	%	D1003
Haze	<4	%	D1003
Clarity	>97	%	D1003
Typical Thermoforming Temperature	250 to 310 (121 to 154)	°F (°C)	
Typical Range of Use	0 to 150 (-18 to 66)	°F (°C)	

CHEMICAL RESISTANCE

Acid Resistance	Good to Excellent
Strong Oxidizers	Good to Excellent
Alkalies	Fair to Good
Hydrocarbon Solvents	Good to Excellent
Alcohols	Good to Excellent
Fat, Grease, and Oil	Good to Excellent

The information herein, is to the best of our knowledge, true, and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. No warranty is made or implied.

FOR MORE INFORMATION CONTACT OUR SALES DEPARTMENT AT 888.456.8018